



COORDINATES SHOWN HEREON ARE BASED ON THE OHIO COORDINATE SYSTEM OF 1983 - NORTH ZONE, 1986 ADJUSTMENT. COUNTY CONTROL POINTS USED: NO. 49 AND 111.

SURVEY LEGEND

- 5/8" IRON PIN SET
- IRON PIN/PIPE FOUND
- ⊞ 5/8" IRON PIN SET IN MONUMENT BOX
- MONUMENT BOX FOUND
- A., ACT. ACTUAL MEASUREMENT OR CALCULATION
- U., USED USED MEASUREMENT OR MONUMENT
- M., MSD MEASURED
- D., R., REC. DEED OR RECORD
- CALC. CALCULATED
- C/L CENTERLINE
- O., OBS. OBSERVED
- P.P.N. PERMANENT PARCEL NUMBER

CURVE TABLE

CURVE	LENGTH	RADIUS	TANGENT	CHORD	BEARING	DELTA
C1	97.23	200.00	49.60	96.28	N74°52'31"W	27°51'20"
C2	159.53	300.00	81.70	157.66	S76°10'54"E	30°28'07"
C3	47.70	320.00	23.90	47.66	N05°06'14"E	8°32'28"
C4	52.23	320.00	26.17	52.17	S04°41'54"W	9°21'08"
C5	111.82	230.00	57.04	110.72	N74°52'31"W	27°51'20"
C6	143.58	270.00	73.53	141.89	S76°10'54"E	30°28'07"
C7	45.95	30.00	28.84	41.59	N44°42'31"E	87°45'02"
C8	52.17	350.00	26.14	52.13	N05°06'14"E	8°32'28"
C9	47.34	290.00	23.72	47.28	S04°41'54"W	9°21'08"
C10	40.07	50.00	21.18	39.01	S22°56'17"E	45°55'15"
C11	75.88	65.00	42.93	71.65	N12°27'13"W	66°53'24"
C12	94.70	65.00	57.99	86.55	N62°43'52"E	83°28'45"
C13	50.00	65.00	26.31	48.78	S53°29'33"E	44°04'25"
C14	64.97	65.00	35.49	62.30	S02°49'22"E	57°15'58"
C15	22.84	65.00	11.54	22.72	S35°52'36"W	20°07'58"
C16	40.07	50.00	21.18	39.01	N22°58'58"E	45°55'15"
C17	57.13	350.00	28.63	57.07	S04°41'54"W	9°21'08"
C18	43.23	290.00	21.66	43.19	N05°06'14"E	8°32'28"
C19	48.30	30.00	31.20	43.25	N45°17'29"W	92°14'58"
C20	122.54	330.00	61.99	121.84	S80°46'40"E	21°16'35"
C21	52.94	330.00	26.53	52.89	S65°32'37"E	91°1'32"
C22	82.65	170.00	42.16	81.84	N74°52'31"W	27°51'20"

LINE TABLE

LINE	LENGTH	BEARING
L1	10.99	S88°48'11"E

